

# Model: SA410LLi Battery powered optical smoke alarm

Compact, battery operated smoke alarm. Advanced microprocessor controlled detection and optimum sensing chamber design combine with the added benefit of an alarm pause feature to provide enhanced resistance to nuisance alarms from sources such as cooking fumes. The alarm is automatically activated during installation and is powered by a non-removable long life battery that will comfortably power the alarm well beyond its 10 year replacement date.



## Product features:

- Long life sealed in lithium battery
- Compact design
- Optical sensing technology
- Alarm pause and test button
- Low battery warning
- Interlinkable - Links up to 12 alarms
- Loud 85dB alarm
- 10 year guarantee
- BS EN 14604: 2005

<b>Model number</b>	SA410LLi
<b>Description</b>	Battery operated smoke alarm
<b>Technology</b>	Optical sensing technology
<b>Sensitivity</b>	In accordance with EN 14604
<b>Alarm sound level</b>	85dB at 3m
<b>Battery type</b>	Lithium battery
<b>Operation AC/DC</b>	DC
<b>Installation positions</b>	Ceiling
<b>Operating temperature</b>	5°C (40°F) to 38°C (100°F)
<b>Operating humidity</b>	10% to 85% relative
<b>Storage temperature</b>	5°C (40°F) to 38°C (100°F)
<b>Storage humidity</b>	10% to 85% relative
<b>Guarantee</b>	10 years

<b>Unit dimensions</b>	37mm(h) x 86mm (dia)
<b>Unit weight</b>	95g
<b>Pack dimensions</b>	165mm (H) x 105mm (W) x 40mm (D)
<b>Pack weight</b>	165g
<b>Master pack quantity</b>	20
<b>Master pack dimensions</b>	-
<b>Master pack weight</b>	-
<b>Pack barcode</b>	5022391064305
<b>Outer barcode</b>	-
<b>Approvals</b>	BS EN 14604: 2005

Please note that specifications may be subject to change at any time.