

Model: M300i 9V battery powered smoke alarm

The Micro 300i Linkable Smoke Alarm can be linked to up to 11 other suitable smoke and heat alarms. This extends security economically over a large area; when one sounds they all do. Pressing the test button confirms that the interconnect is operating.



Product features:

- 9 volt - battery operated
- Can be linked to as many as 11 other suitable battery operated
- alarms
- Low battery warning
- Compact design
- Battery included
- Dual ionization
- Loud piezo electric alarm
- 5 year guarantee (alarm only)
- BS EN 14604: 2005

Model number	M300i
Description	9V smoke alarm with interconnect
Technology	Ionisation
Sensitivity	In accordance with EN14604: 2005
Alarm sound level	85dB at 3m
Battery type	9V alkaline
Operation AC/DC	DC
Installation positions	Ceiling
Operating temperature	5°C (40°F) to 38°C (100°F)
Operating humidity	10% to 85%
Storage temperature	5°C (40°F) to 38°C (100°F)
Storage humidity	10% to 85%
Guarantee	5 years

Unit dimensions	130g
Unit weight	111mm (diameter) x 37mm (height)
Pack dimensions	TBC
Pack weight	137g
Master pack quantity	10
Master pack dimensions	TBC
Master pack weight	TBC
Pack barcode	5022391064244
Outer barcode	15022391064241
Approvals	Certified to BS EN 14604: 2005

Please note that specifications may be subject to change at any time.